

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **63224891 A**(43) Date of publication of application: **19.09.88**

(51) Int. Cl.

B23K 26/00**B23K 26/06****B28D 1/22****// E04G 23/08**(21) Application number: **62059079**(22) Date of filing: **16.03.87**(71) Applicant: **FUJITA CORP KOGYO KAIHATSU
KENKYUSHO**(72) Inventor: **NOJIMA HIROSHI
YOSHIZAWA HIROSHI
SAITO HIDEAKI****(54) CONCRETE CUTTING DEVICE**

easy in its handling can thus be realized.

(57) Abstract

COPYRIGHT: (C)1988,JPO&Japio

PURPOSE: To obtain the concrete cutting device easy in handling with the head part being miniaturized by combining a short focal point concave reflection mirror and long focal point convex reflection mirror and arranging on the optical path of the laser beam to be oscillated as a parallel beam from an oscillating device.

CONSTITUTION: The laser beam L1 oscillated from a laser beam oscillating device 1 as a parallel beam is guided to a laser condensing part C via the orthogonal cylindrical body 4 consisting of an expansion cylindrical body 2 and a rotary mechanism 3. The laser beam L2 condensed by reflecting by the concave reflection mirror 5 having comparatively short focal point is condensed at long focal point by reflecting by a convex reflection mirror 6 so as to obtain the necessary opening angle α . The laser beam L3 thus approached to parallel light is focused on a focal point P toward the necessary position of a concrete construction A. A cooling device 9 having fast heat conduction is provided on the back face of the reflection mirror 6 having high energy density. The concrete cutting whose head part is miniaturized and

